

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification System for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEx BAS 08.0092X** Page 1 of 4

Certificate history:

Status: Current

Issue No: 5

Issue 4 (2015-07-14) Issue 3 (2015-01-14)

Date of Issue:

Applicant:

Equipment:

2022-07-07

Issue 2 (2011-02-03)

Issue 1 (2009-02-05) Issue 0 (2008-10-24)

Via Caboto 19/3 34147 Trieste

Pittway Tecnologica S.r.l.

Italy

22051EISE Photo/Optical Detector

Optional accessory:

Type of Protection: **Intrinsic Safety**

Ex ia IIC T5 Ga (-20°C \leq Ta \leq +40°C) Ex ia IIC T4 Ga (-20°C \leq Ta \leq +60°C) Marking:

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Signature: (for printed version)

(for printed version)

27 July 2022

Technical Manager

1. This certificate and schedule may only be reproduced in full.

This certificate and scriedule may only be reproduced in run.
This certificate is not transferable and remains the property of the issuing body.
The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

SGS Baseefa Limited **Rockhead Business Park** Staden Lane Buxton, Derbyshire, SK17 9RZ **United Kingdom**





IECEx Certificate of Conformity

IECEx BAS 08.0092X Page 2 of 4 Certificate No.:

Date of issue: 2022-07-07 Issue No: 5

Manufacturer: Pittway Tecnologica S.r.l.

Via Caboto 19/3 34147 Trieste

Italy

Pittway Tecnologica S.r.l. Manufacturing

Via Caboto 19/3 locations: 34147 Trieste

Italy

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS:

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements

Edition:7.0

Edition:6.0

IEC 60079-11:2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

This Certificate does not indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

GB/BAS/ExTR08.0198/00 GB/BAS/ExTR08.0245/00 GB/BAS/ExTR11.0023/00 GB/BAS/ExTR22.0009/00 GB/BAS/ExTR14.0369/00 GB/BAS/ExTR15.0185/00

Quality Assessment Report:

GB/BAS/QAR06.0016/10



IECEx Certificate of Conformity

Certificate No.: IECEx BAS 08.0092X Page 3 of 4

Date of issue: 2022-07-07 Issue No: 5

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The 22051EISE Intelligent Photo/Optical Smoke Detector including models TC842B1007 AE, and IDX-751 AE are designed to detect the presence of smoke within a photo electronic sensing chamber and provide a local alarm indication by two LEDs and an alarm signal for connection to a remote control panel via a dedicated Galvanic Isolator with an IST200 Translator Module. Two rotary decade address switches are provided to set the sensor address between 00 and 99. The Detector may be tested for correct operation by use of an external test magnet which actuates an internal reed switch. The Smoke Detector is mounted on a fixed Base Unit Type B501AP which contains the field terminals for connection to the Galvanic Isolator and / or a subsequent Smoke Detector in the daisy chain.

The Smoke Detector comprises an outer plastic cover which has four openings which are protected by a wire gauze screen which permits smoke particles to enter the sensing chamber. Two LEDs are visible externally and provide the local alarm indication. The electronic components are mounted on the underside of a single printed circuit board. Three spring connectors pass the connections between the fixed base unit and the Smoke Detector. The rotary decade address switches are set on installation and are only accessible when the Smoke Detector is separated from the fixed base unit.

 $U_{i} = U_{0} = 28V$

 $I_i = I_o = 94mA$

 $P_i = P_0 = 0.7W$

 $C_i = 0$ $L_i = 0$

SPECIFIC CONDITIONS OF USE: YES as shown below:

1) The 22051EISE Intelligent Photo/Optical Smoke Detector is considered to present an electrostatic hazard and must not be rubbed or cleaned in a hazardous area. A Warning Label is attached:- "Warning Electrostatic Hazard. Do not clean with a dry cloth"



IECEx Certificate of Conformity

Certificate No.: IECEx BAS 08.0092X Page 4 of 4

Date of issue: 2022-07-07 Issue No: 5

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)

Variation 5.1

To confirm that the range of 22051EISE Photo/Optical Detectors comply with the requirements of IEC 60079-0:2018. UKEX Approval.

ExTR: GB/BAS/ExTR22.0009/00 File Reference: 21/0313